

# Technical Details

## Husqvarna 2024 FC450 4 Stroke

### ENGINE

- TRANSMISSION: 5-speed
- BATTERY CAPACITY: 2 Ah
- COOLING: Liquid cooled
- STARTER: Electric starter
- STROKE: 63.4 mm
- BORE: 95 mm
- CLUTCH: Wet, DDS multi-disc clutch, Brembo hydraulics
- DISPLACEMENT: 449.9 cm<sup>3</sup>
- EMS: Keihin EMS
- DESIGN: 1-cylinder, 4-stroke engine

### CHASSIS

- WEIGHT (WITHOUT FUEL): 102.8 kg
- TANK CAPACITY (APPROX.): 7.21
- FRONT BRAKE DISC DIAMETER: 260 mm
- REAR BRAKE DISC DIAMETER: 220 mm
- FRONT BRAKE: Disc brake
- REAR BRAKE: Disc brake
- CHAIN: 520, Non-sealed
- FRAME DESIGN: Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION: WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE: 336 mm
- REAR SUSPENSION: WP XACT Mono-shock with linkage
- SEAT HEIGHT: 939 mm
- STEERING HEAD ANGLE: 63.9°
- SUSPENSION TRAVEL (FRONT): 305 mm
- SUSPENSION TRAVEL (REAR): 293 mm