

# Technical Details

## Husqvarna 2024 Fe 450 4 Stroke

### ENGINE

- TRANSMISSION: 6-speed
- BATTERY CAPACITY: 2 Ah
- COOLING: Liquid-cooled
- STARTER: Electric starter
- STROKE: 63.4 mm
- BORE: 95 mm
- CLUTCH: DDS wet multi-disc clutch, Braktec hydraulics
- DISPLACEMENT: 449.9 cm<sup>3</sup>
- EMS: Keihin EMS
- DESIGN: 1-cylinder, 4-stroke engine

### CHASSIS

- WEIGHT (WITHOUT FUEL): 109.8 kg
- TANK CAPACITY (APPROX.): 8 l
- FRONT BRAKE DISC DIAMETER: 260 mm
- REAR BRAKE DISC DIAMETER: 220 mm
- FRONT BRAKE: Disc brake
- REAR BRAKE: Disc brake
- CHAIN: 520 X-Ring
- FRAME DESIGN: Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION: WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE: 343 mm
- REAR SUSPENSION: WP XACT Monoshock with linkage
- SEAT HEIGHT: 952 mm
- STEERING HEAD ANGLE: 63.9°
- SUSPENSION TRAVEL (FRONT): 300 mm
- SUSPENSION TRAVEL (REAR): 300 mm