

# Technical Details

## 2024 Husqvarna FE 501w Enduro

### ENGINE

- TRANSMISSION 6-speed
- BATTERY CAPACITY 2 Ah
- COOLING Liquid cooled.
- STARTER Electric starter
- STROKE 72 mm
- BORE 95 mm
- CLUTCH DDS wet multi-disc clutch, Braktec hydraulics
- DISPLACEMENT 510.9 cm<sup>3</sup>
- EMS Keihin EMS
- DESIGN 1-cylinder, 4-stroke engine

### CHASSIS

- WEIGHT (WITHOUT FUEL) 112.5 kg
- TANK CAPACITY (APPROX.) 8 l
- FRONT BRAKE DISC DIAMETER 260 mm
- REAR BRAKE DISC DIAMETER 220 mm
- FRONT BRAKE Disc brake
- REAR BRAKE Disc brake
- CHAIN 520 X-Ring
- FRAME DESIGN Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE 343 mm
- REAR SUSPENSION WP XACT Monoshock with linkage
- SEAT HEIGHT 952 mm
- STEERING HEAD ANGLE 63.9 °
- SUSPENSION TRAVEL (FRONT) 300 mm
- SUSPENSION TRAVEL (REAR) 300 mm