

Technical Details

Husqvarna 2024 TC125 2 Stroke

ENGINE

- TRANSMISSION: 6-speed
- BATTERY CAPACITY: 2 Ah
- COOLING: Liquid cooled
- STARTER: Electric starter
- STROKE: 54.5 mm
- BORE: 54 mm
- CLUTCH: Wet multi-disc DS clutch, Brembo hydraulics
- DISPLACEMENT: 124.8 cm³
- EMS: Vitesco Technologies EMS
- DESIGN: 1-cylinder, 2-stroke engine

CHASSIS

- WEIGHT (WITHOUT FUEL): 92.5 kg
- TANK CAPACITY (APPROX.): 7.2 l
- FRONT BRAKE DISC DIAMETER: 260 mm
- REAR BRAKE DISC DIAMETER: 220 mm
- FRONT BRAKE: Disc brake
- REAR BRAKE: Disc brake
- CHAIN: 520, Non-sealed
- FRAME DESIGN: Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION: WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE: 350 mm
- REAR SUSPENSION: WP XACT Monoshock with linkage
- SEAT HEIGHT: 939 mm
- STEERING HEAD ANGLE: 63.9°
- SUSPENSION TRAVEL (FRONT): 305 mm
- SUSPENSION TRAVEL (REAR): 293 mm