

Technical Details

2024 Husqvarna TE 150

ENGINE

- TRANSMISSION: 6-speed
- BATTERY CAPACITY: 2 Ah
- COOLING: Liquid cooled
- STROKE: 54.5 mm
- BORE: 58 mm
- CLUTCH: DS wet multi-disc clutch, Braktec hydraulics
- DISPLACEMENT: 143.99 cm³
- EMS: Vitesco Technologies EMS
- DESIGN: 1-cylinder, 2-stroke engine

CHASSIS

- WEIGHT (WITHOUT FUEL): 100.2 kg
- FRONT BRAKE DISC DIAMETER: 260 mm
- REAR BRAKE DISC DIAMETER: 220 mm
- FRONT BRAKE: Disc brake
- REAR BRAKE: Disc brake
- CHAIN: 520 X-Ring
- FRAME DESIGN: Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION: WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE: 359 mm
- REAR SUSPENSION: WP XACT Mono-shock with linkage
- SEAT HEIGHT: 952 mm
- SUSPENSION TRAVEL (FRONT): 300 mm
- SUSPENSION TRAVEL (REAR): 300 mm