

Technical Details

2024 Husqvarna TE 300

ENGINE

- TRANSMISSION 6-speed
- BATTERY CAPACITY 2 Ah
- COOLING Liquid-cooled
- STROKE 72 mm
- BORE 72 mm
- CLUTCH DDS wet multi-disc clutch, Braktec hydraulics
- DISPLACEMENT 293.2 cm³
- EMS Vitesco Technologies EMS
- DESIGN 1-cylinder, 2-stroke engine

CHASSIS

- WEIGHT (WITHOUT FUEL) 107 kg
- TANK CAPACITY (APPROX.) 8.5 l
- FRONT BRAKE DISC DIAMETER 260 mm
- REAR BRAKE DISC DIAMETER 220 mm
- FRONT BRAKE Disc brake
- REAR BRAKE Disc brake
- CHAIN 520 X-Ring
- FRAME DESIGN Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE 354 mm
- REAR SUSPENSION WP XACT Monoshock with linkage
- SEAT HEIGHT 952 mm
- STEERING HEAD ANGLE 63.9 °
- SUSPENSION TRAVEL (FRONT) 300 mm
- SUSPENSION TRAVEL (REAR) 300 mm