

# Technical Details

## 2024 Husqvarna TE 300 PRO

### ENGINE

- TRANSMISSION 6-speed
- BATTERY CAPACITY 2 Ah
- COOLING Liquid cooled.
- STARTER Electric starter
- STROKE 72 mm
- BORE 72 mm.
- CLUTCH Wet, DDS multi-disc clutch, Brembo hydraulics.
- DISPLACEMENT 293.2 cm<sup>3</sup>
- EMS Vitesco Technologies EMS
- DESIGN 1-cylinder, 2-stroke engine

### CHASSIS

- WEIGHT (WITHOUT FUEL) 108.5 kg
- TANK CAPACITY (APPROX.) 8.5 l
- FRONT BRAKE DISC DIAMETER 260 mm
- REAR BRAKE DISC DIAMETER 220 mm
- FRONT BRAKE Disc brake
- REAR BRAKE Disc brake
- CHAIN 520 X-Ring
- FRAME DESIGN Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE 354 mm
- REAR SUSPENSION WP XACT Monoshock with linkage
- SEAT HEIGHT 952 mm
- STEERING HEAD ANGLE 63.9 °
- SUSPENSION TRAVEL (FRONT) 300 mm
- SUSPENSION TRAVEL (REAR) 300 mm