2027 Husqvarna TE 300 PRO

Technical Specifications

Engine

- Primary Drive: 26:72
- Transmission: 6-speed
- Battery Capacity: 2 Ah
- Cooling System: Liquid-cooled
- Starter: Electric
- Stroke: 2.83 in
- Bore: 2.83 in
- Clutch: Wet, DDS multi-disc clutch with Brembo hydraulic system
- Displacement: 293.2 cc
- Engine Management System: Vitesco Technologies EMS
- Engine Type: Single-cylinder, 2-stroke
- Fuel System: Keihin EFI, 39 mm throttle body

Chassis

- Weight (Without Fuel): 238.8 lb
- Fuel Tank Capacity: 2.25 gal
- Wheelbase: 58.6 in
- Front Brake Rotor Diameter: 10.24 in
- Rear Brake Rotor Diameter: 8.66 in
- Front Brake: Disc brake
- Rear Brake: Disc brake
- Chain: 520 X-Ring
- Frame: 25CrMo4 steel, central double-cradle design
- Front Suspension: WP XACT USD fork, 48 mm

- Ground Clearance: 13.9 in
- Handlebar: Pro Taper aluminum, 28/22 mm
- Rear Suspension: WP XACT monoshock with linkage
- Seat Height: 37.5 in
- Silencer: Aluminum
- Steering Head Angle: 63.9°
- Rear Subframe: Aluminum-reinforced polyamide
- Front Suspension Travel: 11.8 in
- Rear Suspension Travel: 11.8 in
- Tire Sizes (Front/Rear): 90/90-21; 140/80-18
- Wheel Sizes (Front/Rear): 1.60 x 21 in; 2.15 x 18 in