

## 2025 Husqvarna TE 300

### Technical Details (U.S. Metrics)

---

#### Engine

- **Transmission:** 6-speed
  - **Battery Capacity:** 2 Ah
  - **Cooling:** Liquid cooled
  - **Stroke:** 2.83 in
  - **Bore:** 2.83 in
  - **Clutch:** Wet DDS multi-disc clutch, Brembo hydraulics
  - **Displacement:** 17.89 in<sup>3</sup> (293.2 cc)
  - **EMS:** Vitesco Technologies EMS
  - **Engine Design:** 1-cylinder, 2-stroke
  - **Fuel System:** Keihin EFI, 39 mm throttle body
- 

#### Chassis

- **Weight (without fuel):** 235.9 lbs.
  - **Fuel Tank Capacity:** 2.11 gallons (8.0 L)
  - **Wheelbase:** 58.6 in
  - **Ground Clearance:** 13.5 in
  - **Seat Height:** 37.5 in
  - **Steering Head Angle:** 63.9°
  - **Frame:** Central double-cradle-type 25CrMo4 steel
  - **Rear Subframe:** Aluminum-reinforced polyamide
- 

#### Brakes & Suspension

- **Front Brake Disc Diameter:** 10.2 in (260 mm)
  - **Rear Brake Disc Diameter:** 8.7 in (220 mm)
  - **Front Suspension:** WP XACT cartridge Ø 1.89 in (48 mm)
  - **Rear Suspension:** WP XACT Monoshock with linkage
  - **Front Suspension Travel:** 11.8 in
  - **Rear Suspension Travel:** 11.8 in
- 

## Wheels

- **Type:** Spoked wheels with aluminum rims
- **Chain:** 520 X-Ring