

Technical Details

ENGINE

- RATED OUTPUT 2 kW / 3,200 rpm.
- TORQUE 10.5 Nm
- TRACTION BATTERY Lithium-ion
- CHARGER LINE VOLTAGE 80-240 V/50-60 Hz
- CHARGING POWER 900 W
- CHARGING TIME 100 %60 min.
- COOLING Air cooled.
- ELECTRIC MOTOR 48 V - BLDC motor with outer rotor
- MAX. POWER 3.8 kW @ 3,900 RPM

CHASSIS

- FRONT BRAKE DISC DIAMETER 160 mm
- REAR BRAKE DISC DIAMETER 160 mm
- FRONT BRAKE Disc brake
- REAR BRAKE Disc brake
- CHAIN 1/2 x 3/16"
- FRAME DESIGN Chrome-molybdenum steel central-tube frame
- FRONT SUSPENSION XACT 35 WP Upside-Down fork, Ø 35 mm
- GROUND CLEARANCE 152 mm
- REAR SUSPENSION WP Monoshock
- SEAT HEIGHT 555/600 mm
- STEERING HEAD ANGLE 66 °
- SUSPENSION TRAVEL (FRONT) 144 mm
- SUSPENSION TRAVEL (REAR) 133 mm