

Technical Details

ENGINE

- RATED OUTPUT 2 kW / 3,200 rpm.
- TORQUE 13.8 Nm
- TRACTION BATTERY Lithium-ion
- BATTERY CAPACITY 21 Ah
- CHARGER LINE VOLTAGE 80-240 V/50-60 Hz
- CHARGING INPUT Quick charging 5 A @ 230 V (AC)
- CHARGING POWER 900 W
- CHARGING TIME 100 % 70 min.
- CHARGING TIME 80 % 45 min.
- COOLING Air cooled
- ELECTRIC MOTOR 48 V - BLDC motor with outer rotor
- 6000 rpm
- MAX. POWER 5 kW / 3,900 rpm

CHASSIS

- FRONT BRAKE DISC DIAMETER 205 mm
- REAR BRAKE DISC DIAMETER 185 mm
- FRONT BRAKE Disc brake
- REAR BRAKE Disc brake
- CHAIN 1/2 x 3/16"
- FRAME DESIGN Chrome-molybdenum steel central-tube frame
- FRONT SUSPENSION WP-USD, AER 35, Ø 35 mm
- GROUND CLEARANCE 252 mm
- REAR SUSPENSION XACT WP mono shock
- SEAT HEIGHT 665/615 mm
- STEERING HEAD ANGLE 66 °
- SUSPENSION TRAVEL (FRONT) 205 mm
- SUSPENSION TRAVEL (REAR) 185 mm