Technical Details 2024 Husqvarna FC 450

ENGINE

- TRANSMISSION 5-speed
- STARTER Electric starter
- STROKE 63.4 mm
- BORE 95 mm
- CLUTCH Wet, DDS multi-disc clutch, Brembo hydraulics
- DISPLACEMENT 449.9 cm³
- EMS Keihin EMS
- DESIGN 1-cylinder, 4-stroke engine

CHASSIS

- WEIGHT (WITHOUT FUEL) 102.8 kg
- TANK CAPACITY (APPROX.) 7.21
- FRONT BRAKE DISC DIAMETER 260 mm
- REAR BRAKE DISC DIAMETER 220 mm
- FRONT BRAKE Disc brake
- REAR BRAKE Disc brake
- CHAIN 520, Non-sealed
- FRAME DESIGN Central double-cradle-type 25CrMo4 steel
- FRONT SUSPENSION WP XACT-USD, Ø 48 mm
- GROUND CLEARANCE 336 mm
- REAR SUSPENSION WP XACT Monoshock with linkage
- SEAT HEIGHT 939 mm
- STEERING HEAD ANGLE 63.9°
- SUSPENSION TRAVEL (FRONT) 305 mm
- SUSPENSION TRAVEL (REAR) 293 mm