

## 2024 Husqvarna 701 Enduro

### Technical Specifications (U.S. Version)

#### Engine

- **Torque:** 54.2 lb-ft
- **Transmission:** 6-speed
- **Cooling:** Liquid-cooled
- **Horsepower:** Approximately 74 hp (55 kW)
- **Starter:** Electric start
- **Stroke:** 3.15 in
- **Bore:** 4.13 in
- **CO<sub>2</sub> Emissions:** 98 g/km
- **Displacement:** 692.7 cc
- **Engine Management System (EMS):** Keihin EMS with ride-by-wire (RBW), twin ignition
- **Engine Type:** Single-cylinder, 4-stroke
- **Fuel System:** Keihin electronic fuel injection (EFI), 50 mm throttle body
- **Lubrication:** Forced oil lubrication with dual oil pumps

#### Chassis

- **Dry Weight:** 322 lbs
- **Fuel Tank Capacity:** 3.4 gal (approx.)
- **Wheelbase:** 59.3 in
- **ABS:** Bosch 9.1 MP dual-channel ABS (includes Cornering ABS and Supermoto mode, switchable)
- **Front Brake Disc Diameter:** 11.8 in (300 mm)
- **Rear Brake Disc Diameter:** 9.4 in (240 mm)
- **Front Brake:** Brembo twin-piston floating caliper, disc brake
- **Rear Brake:** Brembo single-piston floating caliper, disc brake

- **Chain:** X-Ring 5/8 x 1/4 in
- **Frame Type:** Chromium-molybdenum steel trellis frame, powder-coated
- **Front Suspension:** WP XPLOR-USD forks, 48 mm diameter
- **Ground Clearance:** 10.6 in
- **Handlebar:** Tapered aluminum, Ø 1-1/8" to 7/8" (28/22 mm)
- **Rear Suspension:** WP XPLOR shock with Pro-Lever linkage
- **Seat Height:** 36.4 in
- **Exhaust:** Stainless steel silencer with regulated catalytic converter
- **Steering Head Angle:** 62.3°
- **Rear Subframe:** Self-supporting plastic fuel tank design
- **Front Suspension Travel:** 9.8 in
- **Rear Suspension Travel:** 9.8 in
- **Wheels:** Spoked wheels with aluminum rims