

2026 Husqvarna TC 125

Technical Details

Engine

- **Primary drive:** 23:73 (same)
 - **Transmission:** 6-speed
 - **Battery capacity:** 2 Ah (same)
 - **Cooling:** Liquid-cooled
 - **Secondary gear ratio:** 13:50
 - **Starter:** Electric
 - **Stroke:** 54.5 mm → 2.15 in
 - **Bore:** 54 mm → 2.13 in
 - **Clutch:** Wet multi-disc DS (Brembo hydraulics)
 - **Displacement:** 124.8 cm³ → 7.62 in³
 - **EMS:** Vitesco Technologies EMS
 - **Engine design:** 1-cylinder, 2-stroke
 - **Throttle body:** 39 mm → 1.54 in (Keihin EFI)
-

Chassis

- **Weight (without fuel):** 92.1 kg → 203.1 lbs.
- **Tank capacity:** 7.2 L → 1.90 U.S. gallons
- **Wheelbase:**
 - 1490 mm → 58.66 in
 - (±10 mm → ±0.39 in)
- **Front brake disc:** 260 mm → 10.24 in
- **Rear brake disc:** 220 mm → 8.66 in

- **Front brake:** Disc
- **Rear brake:** Disc
- **Chain:** 520, non-sealed
- **Frame:** 25CrMo4 steel double-cradle
- **Front suspension:** WP XACT-USD, 48 mm → 1.89 in
- **Ground clearance:** 350 mm → 13.78 in
- **Handlebar:** Pro Taper Aluminum
 - Ø 28 mm → 1.10 in
 - Ø 22 mm → 0.87 in
- **Rear suspension:** WP XACT Monoshock w/ linkage
- **Seat height:** 946 mm → 37.24 in
- **Steering head angle:** 63.9°
- **Suspension travel (front):** 305 mm → 12.01 in
- **Suspension travel (rear):** 293 mm → 11.54 in
- **Tire sizes:**
 - Front: 80/100-21
 - Rear: 100/90-19
- **Wheels:**
 - 1.6 × 21" (front)
 - 2.15 × 19" (rear)
- **Wheel type:** Spoked aluminum rims
- **Rear subframe:** Aluminum-reinforced polyamide