

2026 Husqvarna TE 300

Technical Details

Engine

- **Primary drive:** 26:72 (same)
 - **Transmission:** 6-speed
 - **Battery capacity:** 2 Ah (same)
 - **Cooling:** Liquid-cooled
 - **Secondary gear ratio:** 14:50 (same)
 - **Starter:** Electric
 - **Stroke:** 72 mm → 2.83 in
 - **Bore:** 72 mm → 2.83 in
 - **Displacement:** 293.2 cm³ → 17.89 in³
 - **EMS:** Vitesco Technologies EMS
 - **Design:** 1-cylinder, 2-stroke
 - **Fuel-mixture generation:** Keihin EFI, 39 mm → 1.54 in throttle body
-

Chassis

- **Weight (without fuel):** 106.8 kg → 235.5 lbs.
- **Tank capacity:** 8.0 L → 2.11 gallons (U.S.)
- **Wheelbase:**
 - 1489 mm → 58.62 in
 - (±10 mm → ±0.39 in)
- **Front brake disc:** 260 mm → 10.24 in
- **Rear brake disc:** 220 mm → 8.66 in
- **Chain:** 520 X-Ring

- **Frame:** Central double-cradle 25CrMo4 steel
- **Front suspension:** WP XACT, 48 mm → 1.89 in
- **Ground clearance:** 343 mm → 13.50 in
- **Handlebar:** Pro Taper Aluminum, 28/22 mm → 1.10 / 0.87 in
- **Rear suspension:** WP XACT monoshock w/ linkage
- **Seat height:** 952 mm → 37.48 in
- **Steering head angle:** 63.9°
- **Suspension travel (front):** 300 mm → 11.81 in
- **Suspension travel (rear):** 300 mm → 11.81 in
- **Tire dimensions:**
 - Front: 80/100-21
 - Rear: 110/100-18
- **Wheels:**
 - 1.60 × 21" (front)
 - 2.15 × 18" (rear)
- **Wheel type:** Spoked aluminum rims
- **Rear subframe:** Aluminum-reinforced polyamide